


Rheem single stage air handler controls for PSC and ECMX blower motors

48P21-811, 48X21-811

Fast and easy direct OEM replacement for Rheem/RUUD applications



Performance data

Model	48P21-811	48X21-811
Blower motor	PSC	ECMX
Versatility	Replaces 14 controls	Replaces 9 controls
Harness included	Yes to replace 47-00436-04	N/A
Mounting	Drop-in replacement	Drop-in replacement
Fuse	3 AMP	3 AMP
Input voltage	25 VAC, 50/60 Hz	25 VAC, 50/60 Hz
Operating temperature range	-40° to 176°F (40° to 80°C)	-40° to 176°F (40° to 80°C)
Humidity range	5-95% relative humidity (non-condensing)	5-95% relative humidity (non-condensing)
Agency approvals	UL	UL
Limited warranty	1 year	1 year

Timing specifications

Model	Thermostat input	Blower ON delay	Blower OFF delay
48P21-811	G	2 seconds	30 seconds
	W1 or W2	2 seconds	75 seconds
48X21-811	G or Y1	0 seconds	0 seconds
	W1 or W2	0 seconds	45 seconds

48P21-811 cross reference:

Rheem / RUUD Brands

47-100436-01
 47-100436-04
 47-100436-04-03
 47-100436-05
 47-100436-84A (115V Kit)
 47-100436-84D (460V Kit)
 47-100436-84J (208/240V Kit)

White-Rodgers

48P21-111
 48P21-811

48X21-811 cross reference:

Rheem / RUUD Brands

47-100436-02
 47-102077-02
 47-102077-05
 47-102077-05-00
 1139-151
 1139-83-1511A

White-Rodgers

48X21-101
 48X21-111
 48X21-811



Download the app for product information

To learn more, visit copeland.com/white-rodgers

R-4825 ©2024 Copeland LP.

WHITE RODGERS
 by **COPELAND**