



# Technical Data

## Low Temperature Range

Multi Compressor Pack	Model	34M045LK	34M060LK	34M066LK	34M075LK	36M090LK	36M105LK	36M120LK	
Compressor	Model	4ML-15X	4MM-20X	4MT-22X	4MU-25X	6MM-30X	6MT-35X	6MU-40X	
Compressor	Qty	3	3	3	3	3	3	3	
Max Operating Current	A	133.8	147.3	168.3	196.2	225.6	254.4	286.5	
Connections	Suction	∅"	2 x 2 1/8	2 x 2 5/8	2 x 2 5/8	2 x 2 5/8	3 x 2 5/8	3 x 2 5/8	3 x 2 5/8
	Discharge	∅"	1 5/8	1 5/8	1 5/8	1 5/8	2 1/8	2 1/8	2 1/8
Dimensions	Length	mm	3050	3050	3050	3050	3050	3050	3050
	Width	mm	1255	1255	1255	1255	1255	1255	1255
	Height	mm	1950	1950	1950	1950	1950	1950	1950
Weight	kg								
Receiver Station	Volume	L	90	130	130	130	130	160	225
	Inlet	∅"	1 3/8	1 5/8	1 5/8	1 5/8	1 5/8	2 1/8	2 1/8
	Outlet	∅"	1 1/8	1 3/8	1 3/8	1 3/8	1 3/8	1 5/8	1 5/8

Multi Compressor Pack	Model	44M060LK	44M080LK	44M088LK	44M100LK	46M120LK	46M140LK	46M160LK	56M175LK	56M200LK	
Compressor	Model	4ML-15X	4MM-20X	4MT-22X	4MU-25X	6MM-30X	6MT-35X	6MU-40X	6MT-35X	6MU-40X	
Compressor	Qty	4	4	4	4	4	4	4	5	5	
Max Operating Current	A	178.4	196.4	224.4	261.6	300.8	339.2	382.0	424.0	477.5	
Connections	Suction	∅"	2 x 2 5/8	2 x 2 5/8	3 x 2 5/8	3 x 2 5/8	3 x 2 5/8	3 x 3 1/8	3 x 3 1/8	3 x 3 1/8	3 x 3 1/8
	Discharge	∅"	1 5/8	2 1/8	2 1/8	2 1/8	2 1/8	2 1/8	2 5/8	2 5/8	2 5/8
Dimensions	Length	mm	3750	3750	3750	3750	3750	3750	4475	4475	
	Width	mm	1255	1255	1255	1255	1255	1255	1255	1255	
	Height	mm	1950	1950	1950	1950	1950	1950	1950	1950	
Weight	kg										
Receiver Station	Volume	L	130	130	130	160	225	225	225	300	300
	Inlet	∅"	1 5/8	1 5/8	1 5/8	2 1/8	2 1/8	2 1/8	2 1/8	2 5/8	2 5/8
	Outlet	∅"	1 3/8	1 3/8	1 3/8	1 5/8	1 5/8	1 5/8	1 5/8	2 1/8	2 1/8

# Performance Data

# R22 - Medium Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-15	-10	-5	0	-15	-10	-5	0
<b>EMP-34M066MK</b> <i>4MA-22X</i>	40	98.7	122.7	150.3	182.1	38.1	41.1	43.8	45.8
	45	91.8	114.6	141.0	171.6	40.2	43.8	47.0	49.7
	50	84.6	106.5	131.7	160.5	42.3	46.4	50.1	53.3
	55		98.4	122.1	149.7		48.6	52.8	56.7
<b>EMP-34M075MK</b> <i>4MH-25X</i>	40	114.9	141.6	172.8	208.5	45.5	49.1	52.2	54.8
	45	107.1	132.9	162.6	196.8	48.2	52.4	56.1	59.3
	50	99.6	124.2	152.4	184.8	50.7	55.4	59.7	63.6
	55		115.2	141.9	172.5		58.2	63.0	67.5
<b>EMP-34M090MK</b> <i>4MI-30X</i>	40	124.2	152.4	185.1	222.6	50.7	54.9	58.7	62.1
	45	116.1	142.8	173.7	209.4	53.6	58.4	62.7	66.6
	50	107.7	133.2	162.3	195.9	56.4	61.5	66.6	71.1
	55		123.3	150.9	182.7		64.5	70.2	75.3
<b>EMP-34M099MK</b> <i>4MJ-33X</i>	40	139.2	171.0	207.3	249.3	56.9	61.5	65.7	69.6
	45	130.2	160.2	194.7	234.6	60.0	65.4	70.2	74.7
	50	120.6	149.1	182.1	219.6	63.3	69.0	74.7	79.8
	55		138.3	169.2	204.6		72.3	78.6	84.3
<b>EMP-34M105MK</b> <i>4MK-35X</i>	40	158.1	193.8	235.2	282.9	64.5	69.6	74.7	78.9
	45	147.6	181.5	220.8	266.1	68.1	74.1	79.8	84.9
	50	136.8	169.2	206.4	249.0	71.7	78.3	84.6	90.3
	55	126.3	156.6	191.7	232.2	75.0	82.2	89.1	95.7
<b>EMP-36M120MK</b> <i>6MI-40X</i>	40	192.6	238.2	290.4	351.0	77.7	83.7	89.1	93.3
	45	179.4	222.9	273.0	330.0	82.5	89.4	95.4	100.8
	50	166.2	207.6	255.3	310.5	86.7	94.5	101.7	108.0
	55	153.0	192.3	237.3	289.2	90.6	99.3	107.4	114.9
<b>EMP-36M135MK</b> <i>6MJ-45X</i>	40	210.3	261.0	319.5	387.0	87.6	95.4	102.0	107.7
	45	194.7	243.0	298.5	363.0	92.4	101.1	108.9	115.8
	50	179.1	225.0	277.5	337.5	96.9	106.5	115.2	123.6
	55	163.2	206.7	256.5	313.5	100.8	111.3	121.2	130.5
<b>EMP-36M150MK</b> <i>6MK-50X</i>	40	238.5	295.8	361.5	438.0	99.6	108.0	115.8	122.1
	45	220.8	275.4	339.0	411.0	105.0	114.6	123.6	131.4
	50	202.8	255.0	315.0	384.0	109.8	120.6	130.8	140.1
	55	185.1	234.3	290.7	355.5	114.3	126.3	137.4	148.2

# Performance Data

# R22 - Medium Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-15	-10	-5	0	-15	-10	-5	0
<b>EMP-44M088MK</b> <i>4MA-22X</i>	40	131.6	163.6	200.4	242.8	50.8	54.8	58.4	61.0
	45	122.4	152.8	188.0	228.8	53.6	58.4	62.6	66.2
	50	112.8	142.0	175.6	214.0	56.4	61.8	66.8	71.0
	55		131.2	162.8	199.6		64.8	70.4	75.6
<b>EMP-44M100MK</b> <i>4MH-25X</i>	40	153.2	188.8	230.4	278.0	60.6	65.4	69.6	73.0
	45	142.8	177.2	216.8	262.4	64.2	69.8	74.8	79.0
	50	132.8	165.6	203.2	246.4	67.6	73.8	79.6	84.8
	55		153.6	189.2	230.0		77.6	84.0	90.0
<b>EMP-44M120MK</b> <i>4MI-30X</i>	40	165.6	203.2	246.8	296.8	67.6	73.2	78.2	82.8
	45	154.8	190.4	231.6	279.2	71.4	77.8	83.6	88.8
	50	143.6	177.6	216.4	261.2	75.2	82.0	88.8	94.8
	55		164.4	201.2	243.6		86.0	93.6	100.4
<b>EMP-44M132MK</b> <i>4MJ-33X</i>	40	185.6	228.0	276.4	332.4	75.8	82.0	87.6	92.8
	45	173.6	213.6	259.6	312.8	80.0	87.2	93.6	99.6
	50	160.8	198.8	242.8	292.8	84.4	92.0	99.6	106.4
	55		184.4	225.6	272.8		96.4	104.8	112.4
<b>EMP-44M140MK</b> <i>4MK-35X</i>	40	210.8	258.4	313.6	377.2	86.0	92.8	99.6	105.2
	45	196.8	242.0	294.4	354.8	90.8	98.8	106.4	113.2
	50	182.4	225.6	275.2	332.0	95.6	104.4	112.8	120.4
	55	168.4	208.8	255.6	309.6	100.0	109.6	118.8	127.6
<b>EMP-46M160MK</b> <i>6MI-40X</i>	40	256.8	317.6	387.2	468.0	103.6	111.6	118.8	124.4
	45	239.2	297.2	364.0	440.0	110.0	119.2	127.2	134.4
	50	221.6	276.8	340.4	414.0	115.6	126.0	135.6	144.0
	55	204.0	256.4	316.4	385.6	120.8	132.4	143.2	153.2
<b>EMP-46M180MK</b> <i>6MJ-45X</i>	40	280.4	348.0	426.0	516.0	116.8	127.2	136.0	143.6
	45	259.6	324.0	398.0	484.0	123.2	134.8	145.2	154.4
	50	238.8	300.0	370.0	450.0	129.2	142.0	153.6	164.8
	55	217.6	275.6	342.0	418.0	134.4	148.4	161.6	174.0
<b>EMP-46M200MK</b> <i>6MK-50X</i>	40	318.0	394.4	482.0	584.0	132.8	144.0	154.4	162.8
	45	294.4	367.2	452.0	548.0	140.0	152.8	164.8	175.2
	50	270.4	340.0	420.0	512.0	146.4	160.8	174.4	186.8
	55	246.8	312.4	387.6	474.0	152.4	168.4	183.2	197.6
<b>EMP-56M225MK</b> <i>6MJ-45X</i>	40	350.5	435.0	532.5	645.0	146.0	159.0	170.0	179.5
	45	324.5	405.0	497.5	605.0	154.0	168.5	181.5	193.0
	50	298.5	375.0	462.5	562.5	161.5	177.5	192.0	206.0
	55	272.0	344.5	427.5	522.5	168.0	185.5	202.0	217.5
<b>EMP-56M250MK</b> <i>6MK-50X</i>	40	397.5	493.0	602.5	730.0	166.0	180.0	193.0	203.5
	45	368.0	459.0	565.0	685.0	175.0	191.0	206.0	219.0
	50	338.0	425.0	525.0	640.0	183.0	201.0	218.0	233.5
	55	308.5	390.5	484.5	592.5	190.5	210.5	229.0	247.0

# Performance Data

# R404A - Medium Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-15	-10	-5	0	-15	-10	-5	0
<b>EMP-34M066MK</b> <i>4MA-22X</i>	40	100.2	125.1	153.9	187.2	43.4	46.5	49.4	51.5
	45	90.0	113.1	140.1	171.6	45.5	49.4	52.8	55.7
	50	80.1	101.4	126.6	156.0	47.4	52.1	56.1	59.7
	55	70.2	90.0	113.4	140.7	49.1	54.5	59.3	63.6
<b>EMP-34M075MK</b> <i>4MH-25X</i>	40	117.0	146.7	181.2	221.7	51.3	55.4	58.8	61.2
	45	105.3	133.2	165.6	203.7	53.6	58.5	62.7	66.3
	50	93.9	119.4	149.7	185.4	55.8	61.5	66.6	70.8
	55	81.9	105.6	133.8	167.1	57.8	64.2	70.2	75.3
<b>EMP-34M090MK</b> <i>4MI-30X</i>	40	131.4	162.9	199.2	241.2	56.9	61.2	64.8	67.8
	45	119.1	148.2	182.1	221.7	59.9	64.8	69.3	73.2
	50	106.2	133.2	164.7	201.6	62.7	68.4	73.8	78.3
	55	93.0	117.9	147.0	181.5	65.1	72.0	78.0	83.4
<b>EMP-34M099MK</b> <i>4MJ-33X</i>	40	146.4	182.1	224.1	273.0	63.3	68.4	72.6	76.2
	45	131.7	165.0	204.0	249.6	66.3	72.3	77.4	81.9
	50	117.0	147.3	183.6	225.9	68.7	75.6	81.9	87.3
	55	102.0	129.9	162.9	202.2	70.8	78.6	85.8	92.1
<b>EMP-34M105MK</b> <i>4MK-35X</i>	40	164.1	204.6	252.3	307.5	73.2	79.2	84.6	89.1
	45	147.6	185.4	229.5	281.4	76.2	83.4	89.7	95.1
	50	130.8	165.3	206.4	254.7	79.2	87.0	94.2	100.5
	55	113.4	144.9	182.7	227.4	81.3	90.0	98.1	105.6
<b>EMP-36M120MK</b> <i>6MI-40X</i>	40	197.4	246.3	303.0	369.0	87.3	93.9	99.6	104.7
	45	178.5	223.8	277.2	339.0	91.8	99.3	106.2	112.5
	50	159.0	201.0	250.5	309.0	96.0	104.7	112.8	120.0
	55	139.5	177.9	223.5	277.5	99.9	109.8	118.8	127.2
<b>EMP-36M135MK</b> <i>6MJ-45X</i>	40	221.1	275.1	339.0	412.5	97.5	104.4	110.4	115.8
	45	199.5	249.6	309.0	378.0	102.9	111.0	118.2	124.5
	50	177.3	223.2	277.5	342.0	108.0	117.6	126.0	133.5
	55	154.8	196.5	246.3	306.0	112.5	123.6	133.5	142.5
<b>EMP-36M150MK</b> <i>6MK-50X</i>	40	247.5	307.5	378.0	459.0	111.6	120.6	129.0	136.8
	45	223.5	279.9	345.0	423.0	117.0	127.2	137.1	146.1
	50	198.6	250.8	312.0	384.0	121.5	133.2	144.3	154.8
	55	173.4	221.1	277.8	345.0	125.4	138.6	151.2	163.2

# Performance Data

# R404A - Medium Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-15	-10	-5	0	-15	-10	-5	0
<b>EMP-44M088MK</b> <i>4MA-22X</i>	40	133.6	166.8	205.2	249.6	57.8	62.0	65.8	68.6
	45	120.0	150.8	186.8	228.8	60.6	65.8	70.4	74.2
	50	106.8	135.2	168.8	208.0	63.2	69.4	74.8	79.6
	55	93.6	120.0	151.2	187.6	65.4	72.6	79.0	84.8
<b>EMP-44M100MK</b> <i>4MH-25X</i>	40	156.0	195.6	241.6	295.6	68.4	73.8	78.4	81.6
	45	140.4	177.6	220.8	271.6	71.4	78.0	83.6	88.4
	50	125.2	159.2	199.6	247.2	74.4	82.0	88.8	94.4
	55	109.2	140.8	178.4	222.8	77.0	85.6	93.6	100.4
<b>EMP-44M120MK</b> <i>4MI-30X</i>	40	175.2	217.2	265.6	321.6	75.8	81.6	86.4	90.4
	45	158.8	197.6	242.8	295.6	79.8	86.4	92.4	97.6
	50	141.6	177.6	219.6	268.8	83.6	91.2	98.4	104.4
	55	124.0	157.2	196.0	242.0	86.8	96.0	104.0	111.2
<b>EMP-44M132MK</b> <i>4MJ-33X</i>	40	195.2	242.8	298.8	364.0	84.4	91.2	96.8	101.6
	45	175.6	220.0	272.0	332.8	88.4	96.4	103.2	109.2
	50	156.0	196.4	244.8	301.2	91.6	100.8	109.2	116.4
	55	136.0	173.2	217.2	269.6	94.4	104.8	114.4	122.8
<b>EMP-44M140MK</b> <i>4MK-35X</i>	40	218.8	272.8	336.4	410.0	97.6	105.6	112.8	118.8
	45	196.8	247.2	306.0	375.2	101.6	111.2	119.6	126.8
	50	174.4	220.4	275.2	339.6	105.6	116.0	125.6	134.0
	55	151.2	193.2	243.6	303.2	108.4	120.0	130.8	140.8
<b>EMP-46M160MK</b> <i>6MI-40X</i>	40	263.2	328.4	404.0	492.0	116.4	125.2	132.8	139.6
	45	238.0	298.4	369.6	452.0	122.4	132.4	141.6	150.0
	50	212.0	268.0	334.0	412.0	128.0	139.6	150.4	160.0
	55	186.0	237.2	298.0	370.0	133.2	146.4	158.4	169.6
<b>EMP-46M180MK</b> <i>6MJ-45X</i>	40	294.8	366.8	452.0	550.0	130.0	139.2	147.2	154.4
	45	266.0	332.8	412.0	504.0	137.2	148.0	157.6	166.0
	50	236.4	297.6	370.0	456.0	144.0	156.8	168.0	178.0
	55	206.4	262.0	328.4	408.0	150.0	164.8	178.0	190.0
<b>EMP-46M200MK</b> <i>6MK-50X</i>	40	330.0	410.0	504.0	612.0	148.8	160.8	172.0	182.4
	45	298.0	373.2	460.0	564.0	156.0	169.6	182.8	194.8
	50	264.8	334.4	416.0	512.0	162.0	177.6	192.4	206.4
	55	231.2	294.8	370.4	460.0	167.2	184.8	201.6	217.6
<b>EMP-56M225MK</b> <i>6MJ-45X</i>	40	368.5	458.5	565.0	687.5	162.5	174.0	184.0	193.0
	45	332.5	416.0	515.0	630.0	171.5	185.0	197.0	207.5
	50	295.5	372.0	462.5	570.0	180.0	196.0	210.0	222.5
	55	258.0	327.5	410.5	510.0	187.5	206.0	222.5	237.5
<b>EMP-56M250MK</b> <i>6MK-50X</i>	40	412.5	512.5	630.0	765.0	186.0	201.0	215.0	228.0
	45	372.5	466.5	575.0	705.0	195.0	212.0	228.5	243.5
	50	331.0	418.0	520.0	640.0	202.5	222.0	240.5	258.0
	55	289.0	368.5	463.0	575.0	209.0	231.0	252.0	272.0

# Performance Data

# R404A - Low Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-40	-35	-30	-25	-40	-35	-30	-25
<b>EMP-34M045LK</b> <i>4ML-15X</i>	40	28.7	40.8	55.2	72.6	27.4	32.6	37.7	42.9
	45	24.5	35.7	48.9	64.8	27.7	33.0	38.6	44.3
	50	20.3	30.5	42.6	57.2	27.9	33.5	39.3	45.3
	55	16.2	25.4	36.3	49.4	28.1	33.8	39.9	46.2
<b>EMP-34M060LK</b> <i>4MM-20X</i>	40	33.3	46.7	62.4	81.3	30.9	36.3	41.9	47.3
	45	28.4	40.7	55.2	72.3	31.1	36.9	43.1	48.9
	50	23.6	34.8	47.9	63.3	30.8	37.4	43.8	50.4
	55	18.9	28.8	40.5	54.5	30.3	37.4	44.4	51.6
<b>EMP-34M066LK</b> <i>4MT-22X</i>	40	37.8	52.4	69.9	90.9	35.0	41.1	47.4	53.7
	45	32.6	45.8	61.8	81.3	35.1	41.9	48.6	55.5
	50	27.2	39.2	53.7	71.4	35.0	42.2	49.5	57.0
	55	22.0	32.6	45.6	61.5	34.7	42.2	50.1	58.2
<b>EMP-34M075LK</b> <i>4MU-25X</i>	40	41.1	57.2	76.5	100.2	39.2	46.2	53.6	60.9
	45	35.4	50.0	67.8	89.4	39.3	47.0	54.6	62.4
	50	29.9	42.8	58.7	78.0	39.2	47.1	55.4	63.6
	55	24.5	35.6	49.5	66.6	38.7	47.0	55.7	64.5
<b>EMP-36M090LK</b> <i>6MM-30X</i>	40	50.7	69.9	93.0	120.9	48.6	57.2	65.7	73.5
	45	43.8	61.5	82.5	108.3	48.8	58.2	67.5	76.5
	50	36.8	53.0	72.0	95.4	48.0	58.5	68.7	78.9
	55	29.6	44.3	61.5	82.2	46.5	57.9	69.3	80.4
<b>EMP-36M105LK</b> <i>6MT-35X</i>	40	57.2	78.6	105.0	137.1	53.3	62.7	72.3	81.9
	45	49.5	69.0	92.7	122.1	53.6	63.9	74.4	84.9
	50	41.9	59.1	80.4	106.8	53.7	64.8	75.9	87.6
	55	34.4	49.4	68.1	91.5	53.6	65.4	77.4	90.0
<b>EMP-36M120LK</b> <i>6MU-40X</i>	40	62.7	87.0	116.7	152.7	60.3	70.8	81.6	92.4
	45	54.3	76.5	103.8	136.5	60.3	72.0	84.0	95.4
	50	45.8	66.0	90.6	120.3	59.9	72.6	85.5	98.1
	55	37.2	55.4	77.4	104.1	58.5	72.0	86.1	99.9

# Performance Data

# R404A - Low Temp

Multi Compressor Pack Model	Condensing Temperature (°C)	Capacity (kW)				Power Input (kW)			
		Evaporating Temperature (°C)							
		-40	-35	-30	-25	-40	-35	-30	-25
<b>EMP-44M060LK</b> <i>4ML-15X</i>	40	38.3	54.4	73.6	96.8	36.6	43.4	50.2	57.2
	45	32.7	47.6	65.2	86.4	36.9	44.0	51.4	59.0
	50	27.1	40.6	56.8	76.2	37.2	44.6	52.4	60.4
	55	21.6	33.8	48.4	65.8	37.4	45.0	53.2	61.6
<b>EMP-44M080LK</b> <i>4MM-20X</i>	40	44.4	62.2	83.2	108.4	41.2	48.4	55.8	63.0
	45	37.9	54.2	73.6	96.4	41.4	49.2	57.4	65.2
	50	31.5	46.4	63.8	84.4	41.0	49.8	58.4	67.2
	55	25.2	38.4	54.0	72.6	40.4	49.8	59.2	68.8
<b>EMP-44M088LK</b> <i>4MT-22X</i>	40	50.4	69.8	93.2	121.2	46.6	54.8	63.2	71.6
	45	43.4	61.0	82.4	108.4	46.8	55.8	64.8	74.0
	50	36.2	52.2	71.6	95.2	46.6	56.2	66.0	76.0
	55	29.4	43.4	60.8	82.0	46.2	56.2	66.8	77.6
<b>EMP-44M100LK</b> <i>4MU-25X</i>	40	54.8	76.2	102.0	133.6	52.2	61.6	71.4	81.2
	45	47.2	66.6	90.4	119.2	52.4	62.6	72.8	83.2
	50	39.9	57.0	78.2	104.0	52.2	62.8	73.8	84.8
	55	32.6	47.4	66.0	88.8	51.6	62.6	74.2	86.0
<b>EMP-46M120LK</b> <i>6MM-30X</i>	40	67.6	93.2	124.0	161.2	64.8	76.2	87.6	98.0
	45	58.4	82.0	110.0	144.4	65.0	77.6	90.0	102.0
	50	49.0	70.6	96.0	127.2	64.0	78.0	91.6	105.2
	55	39.5	59.0	82.0	109.6	62.0	77.2	92.4	107.2
<b>EMP-46M140LK</b> <i>6MT-35X</i>	40	76.2	104.8	140.0	182.8	71.0	83.6	96.4	109.2
	45	66.0	92.0	123.6	162.8	71.4	85.2	99.2	113.2
	50	55.8	78.8	107.2	142.4	71.6	86.4	101.2	116.8
	55	45.8	65.8	90.8	122.0	71.4	87.2	103.2	120.0
<b>EMP-46M160LK</b> <i>6MU-40X</i>	40	83.6	116.0	155.6	203.6	80.4	94.4	108.8	123.2
	45	72.4	102.0	138.4	182.0	80.4	96.0	112.0	127.2
	50	61.0	88.0	120.8	160.4	79.8	96.8	114.0	130.8
	55	49.6	73.8	103.2	138.8	78.0	96.0	114.8	133.2
<b>EMP-56M175LK</b> <i>6MT-35X</i>	40	95.3	131.0	175.0	228.5	88.8	104.5	120.5	136.5
	45	82.5	115.0	154.5	203.5	89.3	106.5	124.0	141.5
	50	69.8	98.5	134.0	178.0	89.5	108.0	126.5	146.0
	55	57.3	82.3	113.5	152.5	89.3	109.0	129.0	150.0
<b>EMP-56M200LK</b> <i>6MU-40X</i>	40	104.5	145.0	194.5	254.5	100.5	118.0	136.0	154.0
	45	90.5	127.5	173.0	227.5	100.5	120.0	140.0	159.0
	50	76.3	110.0	151.0	200.5	99.8	121.0	142.5	163.5
	55	62.0	92.3	129.0	173.5	97.5	120.0	143.5	166.5