

Universal Single Stage Furnace Control for ECMx Blower Motors

50X57-843



The industry's only universal control for ECMx blower motors



Universal Replacement

Services Carrier, Lennox, Trane and York models

Reduce inventory and save time by eliminating extra trips



Easy Installation

Mounting design fits all OEM models

Simple Rollout jumper

Factory wiring plugs directly into the control

24V or 120V humidifier



Advanced Diagnostics

Simple pushbutton fault recall

Tri-Color LED & status codes

Flame current test pins

Fault code label on control



Universal Single Stage Furnace Control for ECMx Blower Motors

50X57-843 The industry's only universal control for ECMx blower motors

SPECIFICATIONS:

Electrical Rating [@ 77°F (25°C)]

Input Voltage: 25 VAC 50/60 Hz
Max Input Current: 0.8 amp @ 25 VAC

Flame Current Requirements

Minimum current to insure flame detection: .31 μ a DC*
Maximum current for non-detection: 0.1 μ a DC*
Maximum allowable leakage resistance: 100 M ohms

* Measuring with a DC voltmeter (1 VDC = 1 μ a)

Operating Temperature Range

-40° to 176° F (-40° to 80° C)

Timing Specifications

(All times are in seconds unless noted otherwise)

Pre-purge	Ignitor warm-up (adaptive, starts at 17)	Retries	Post-purge	Lockout time	Heat ON delay	Heat OFF delay	Cool ON delay	Cool OFF delay	Auto reset	Flame establishment	Flame failure response
15	5-21	3 times	15	250 (seconds)	25	60/90/120*/180	3	3/90*	60 mins	0.8	2.5

* Denotes factory default

Humidity Range

5 - 95% relative humidity (non-condensing)

Gases Approved

Natural, Manufactured, Mixed, Liquefied Petroleum, and LP Gas-Air Mixtures are all approved for use

Dimensions

5.625" W x 8.25" L x 1.50" D (with tabs)
5.25" W x 7.25" L x 1.50" D (tabs removed)

Agency Approvals

UL

1 Year Limited Warranty

50X57-843 CROSS REFERENCE REPLACEMENT:

Carrier / ICP Brands

1183386
1184412
CEPL130934-01
CEPL130934-02
CEPL131011-01
CEPL131011-02
HK42FZ027
HK42FZ033
HK42FZ039
HK42FZ047

Grainger

115Z36
115Z39
116J02

Johnstone

L45-086

Lennox Brands

103217-01
103217-02

607436-01
607436-02
79W84
85W79

Trane / American Standard Brands

CNT04711
CNT06664
CNT07737
CNT07738

D342359P01
D342359P02
D342359P03
D342359P04

White-Rodgers

50A67-476-01
50A67-476-02
50A67-507-01
50A67-507-02
50X57-843

York / JCI Brands

542760
S1 03102951001

80V application which requires 120V ignitor upgrade*

*Suggested upgrade is our HotRod™ Ignitor

The White-Rodgers Mobile App:

- Cross referencing
- Product information
- Product selection



R-4822-2 (11/19)

©2019 Emerson Electric Co. • White-Rodgers and Emerson are trademarks of Emerson Electric Co. All rights reserved • Customer Service or Technical Help: 888-725-9797

Emerson.com/White-Rodgers