


Multi-Function Thermometer

Software Integrations

Multi-Function Thermometer (MFT)

- Temperature Range: 100° to 1000°F (73° to 538°C)
- Accuracy: $\pm 0.5^{\circ}\text{F}$ ($\pm 0.3^{\circ}\text{C}$) at ambient between 68° to 86°F (20° to 30°C). Add ± 0.1 to accuracy spec per 1 change to ambient temperature outside of 68° to 86°F
- Ambient Operating Range: 4° to 122°F (20° to 50°C), 10% to 90% RH, non-condensing
- Resolution: 0.1°F/0.1°C
- Bluetooth Low Energy 2.4 GHz
- RF Range: 100 ft open field range
- Power: (1) AA Alkaline battery
- Battery Life: 500 hours
- 5-year Limited Warranty
- IPX7 waterproof rated



DFS Software Compatibility

The MFT thermometer is integrated with the following 3rd party digital food safety software providers:

- | | |
|----------------------------|---------------------------|
| • Michi (in China) | • iCertainty |
| • Joywok (in China) | • iAuditor (in Australia) |
| • Redzone (in US) | • Jolt |
| • Codemax (in Malaysia) | • Measure Up |
| • Compliance Metrix | • Ops Analytica |
| • Compliance Mate | • Probiz |
| • Cosmos 21 (in Australia) | • Powerhouse Dynamics |
| • Crunchtime | • Squadle |
| • Ecolab | • Squizify (in Australia) |
| • EZ Forms | • Zenput |
| • Frameworks | • Diversey |
| • Fusion Prep | • Procuro |
| • Go Spot Check | • Rizepoint |
| • Hot Schedules | |

