
# **Connect+**

# Food Quality Reports User Guide





### **TABLE OF CONTENTS**

1.	Food Quality Reports Overview	1
2.	Get Started with FQR	2
	2.1 Feature Activation	
	2.2 Full List of FQR Properties	
3.	Configure Food Quality Report	4
4.	FQR Data Gathering	7
	4.1 Schedule FQR Data Gathering	7
	4.2 Run FQR Data Gathering One Time	7
5.	FQR Report Generator	8
	5.1 Report Generation Activity	8
	5.2 Food Quality Report for Yesterday	
	5.3 Reading the FQR Report	. 10
6.	FQR Report Emailing	. 12
	6.1 FQR Full Report Email	
	6.2 FQR Summary Email	
	6.3 FQR Exception Email	. 16
7.	Auto-Fix Previous Reports	. 17

# 1. Food Quality Reports Overview

Connect+ Food Quality Reports (FQR) help to detect if the case temperature is too high or too low and facilitate the automatic reporting for the purpose of keeping the food safe.

With Connect+ Food Quality Reports, user would have capability to:

- Configure the case High/Low limit.
- Generate FQR report for the site.
- Email the report to the right person.

This document serves as a guide for on-boarding new customers to Connect+ Food Quality Reports (FQR). The screens presented in this guide will help you identify the necessary changes to make and where to configure in FQR. Note that due to user permission settings, some screens may be hidden. The Connect+ user configuring FQR must have administrator access to the system and must log in to view the appropriate properties. The Food Quality Reports license must also be enabled to set up any configuration related to FQR. The FQR is generated based on the circuits in a site, including both Standard, Case Control, and XM Circuits. Currently, FQR is supported in E2 and Site Supervisor controllers.

These are the supported peripheral equipment types for each type of supported case controller:

Case Controller Name	Case Temp Supported	2nd Case Temp Supported	Discharge Air Supported	Product Temp Supported	2nd Value Kit Supported
CC100-P (Liquid Pulse)	Yes	Yes	Yes	Yes	Yes - through Discharge Air Support
CC100-LS (Liquid Stepper)	Yes	Yes	Yes	Yes	No
CS 100	Yes	Yes	Yes	Yes	No
EC2-39X	Yes (called Air Temp on this controller type)	No	Yes (called Air In on this controller type)	No-Level 5 access required (not supported)	No
CCB Liquid Pulse	Yes	No	Yes	No	Yes
CCB Liquid Stepper	Yes	No	Yes	No	No
CCB Suction	Yes	No	Yes	No	No

# 2. Get Started with FQR

### 2.1 Feature Activation

Contact Copeland Administrator to first activate the Feature Licensing for FQR.

Click Top Menu > Admin Tools > Feature Activation to check the feature licensing is enabled.

#### Instructions

Contact Copeland at (770) 425-2724 to obtain feature licenses.
 Select the Add Feature button to add or update a feature license.

·		
Feature Licenses	Status	Кеу
Maintenance Upgrades & Tech Support (Expires: 04-08-2022 CDT)	360 Day(s) Remain	CC78-0AE4-D0C2-0161
Connect+	Enabled	155A-C04C-76D0-3B89
Number of Sites (31889 of 32000 Sites Remain )	32000	0CC4-F0F1-6DB1-76FA
Graphical Status & Floorplan Creation Tool	Enabled	F8EE-4C65-6025-2784
Connect+ Advisory Receiver	Enabled	7A1A-5759-2FA5-35CD
Connect+ Data Acquisition	Enabled	DE01-6CF1-84A7-6A38
Number of Connections for TCP/IP	1000	50B3-2C0F-E05E-78CA
Number of Connections for ISDN	1000	9482-5E47-5B8D-25DA
Setpoint Broadcast	Enabled	AEFD-F737-2015-CE32
Demand Response	Enabled	369A-C37A-667A-9293
Refrigerant Tracking	Enabled	6554-9EFF-4D62-84C0
Number of Danfoss Control Systems	32000	C02B-5CC9-7675-0F3F
Reporting: Report Data Collection	2	8224-9ADD-F263-00F7
Food Quality Reports	Enabled	419E-02DC-8A3F-74F1
Number of TAC Xenta 401 Control Systems	32000	23AF-9647-0A21-C420
Scalability Test	Enabled	0BB9-8C39-B864-E857
CB Maintenance Test Utility	Enabled	9CE6-65FE-1CE7-D524
Energy	Enabled	BBC4-4A1A-9B2A-812A
Test Site Conditions	Enabled	F52F-5843-0C46-2998

Feature Licensing

# 2.2 Full List of FQR Properties

To enable FQR and configure certain functions, some properties must be set by the administrator in the Superuser property. Login with Superuser permissions, access the property page from **Top Menu > Super User > Properties Editor**.

#### Table 1: List of FQR Properties

	Property Name	Default Value	Meaning
FQRSystemConfigs	SendDetailsAsAttachment	false	If there is too much information in the Detail Exception Email or if it is too large, set this to "true" and the information on the FQR Detail Summary Email will be sent as a separate attachment.
FQRSystemConfigs	displayFQRSiteAddress	false	Enable this property to show the site address in the FQR report.
FQRSystemConfigs	label.summaryEmail.instanceName		Enter a unique name that describes which instance the email is from. It will show in the report name.
FQRSystemConfigs	report.DisplayDefrostOnDischargeAir	false	Set to "true" if the customer wants to display defrost information on the report where the Discharge Air item is.
FQRSystemConfigs	minimumDefrostMinutesAllow edInHour	10 (mins)	The minimum duration that defrost activities take. If it is less than the configuration, the report will not show defrost status.

#### Table 1: List of FQR Properties


	Property Name	Default Value	Meaning
FQRSystemConfigs	report.defrost.log.image		Path to the image used on the report that will show for a logged defrost.
FQRSystemConfigs	report.defrost.value.image		Path to the image used on the report for a scheduled defrost.
*FQRSystemConfigs	report.email.attachments.limit.maxKB	3000	The maximum size (in KB) an attachment can be for reports. This is to conform to the email size restrictions that a server may have.
*FQRSystemConfigs	report.email.exceptionsReports.recipients		Detail Exception recipient email addresses, each separated by a comma.
*FQRSystemConfigs	report.email.exceptionsReportsSummary. recipients		Summary recipient email addresses, each separated by a comma.
*FQRSystemConfigs	report.email.from		The "From" email address for emails. Usually for Copeland hosted, this is set to: noreply@copeland.com
FQRSystemConfigs	report.email.fullReports.default.recipient.emails		Email address(es) that will be the default recipients of the full reports email on the configuration page.
FQRSystemConfigs	report.email.fullReports.default.recipient.userIDs		User ID of the user who will be the default recipient for full reports from the configuration page.
*FQRSystemConfigs	report.email.isEmailExceptionsReports	true	Set to "true" if the system should email the Detail Summary emails. If this is "false," no emails for Detail Summary will be sent.
*FQRSystemConfigs	report.email.isEmailExceptionsReportsSummary	true	Set to "true" if the system should email the Summary emails. If this is "false," no emails for Detail Summary will be sent.
*FQRSystemConfigs	report.email.minNeedBeZippedReportsCount	4	If the number of reports is equal or more than this number, all of the reports will be zipped and sent as an attachment to the email.
FQRSystemConfigs	report.row.label.prefix.caseTemp	case	Allows the label on the Food Quality Report itself to be changed for Case Temp. Note: The label will be reflected on the FQRs that are run after this change is made.
FQRSystemConfigs	report.row.label.prefix.dischargeAir	Disch Air	Allows the label on the Food Quality Report itself to be changed for Discharge Air. Note: The label will be reflected on the FQRs that are run after this change is made.
FQRSystemConfigs	eport.row.label.prefix.productProbe	Product	Allows the label on the Food Quality Report itself to be changed for Product Probes. Note: The label will be reflected on the FQRs that are run after this change is made

# 3. Configure Food Quality Report

There are defaults for all items in the FQR Configuration screen, but most likely, you will want to view and change some of the configurations.

To navigate to the Food Quality Report Configuration page, right-click on one tree node from the Directory to the Application Instance level, select **Food Quality > Configure Food Quality Report**.

**NOTE**: The configuration menu on Standard, Case Control, XM Circuits and supported peripheral equipment types are only visible.



Configure Food Quality Report

tivity Food Quality Report Configuration	
em Demo	
Use default values below which are the global default value	
Use default values below which are the global default value	a.
Included in Food Quality Report	High/Low Limit Rules List
Logo file: Default	-> If the setpoint is Less than or equal to -9.4 $^{\rm OF}$ , then threshold is +/- 9 $^{\rm OF}$ from the setpoint .
	-> If the setpoint is Between (exclusive) -9.4 °F and -4 °F , then threshold is +/- 5.4 °F from the setpoint .
	-> If the setpoint is Between (inclusive) -4 °F and 68 °F , then threshold is +/- 3.6 °F from the setpoint .
	-> If the setpoint is Greater than 68 $^{\rm OF}$ , then threshold is +/- 18 $^{\rm OF}$ from the setpoint .
	FQR reports currently being emailed to these users:
PR	
Exclude from the Report Generation for FQR	Use rules below for calculating High and Low Limit Copy default rules now
	Bise fixed values for high and bow binne
Include Product Simulator Probes	
Include Product Simulator Probes	Add
Include Product Simulator Probes	Add If the setpoint is Less than or equal to ✓ 9.4 °F then boundary is +/-9 °F⊗
_	
_	If the setpoint is Less than or equal to V -9.4 OF then boundary is +/-9
_	If the setpoint is Less than or equal to v 9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v 9.4 °F and 4 °F then boundary is +/-5.4 °F S
Include all Discharge Air configured	If the setpoint is Less than or equal to v 9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v -9.4 °F and -4 °F then boundary is +/-5.4 °F S If the setpoint is Between (inclusive) v -4 °F and 68 °F then boundary is +/-3.6 °F S
Include all Discharge Air configured	If the setpoint is Less than or equal to v 9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v -9.4 °F and -4 °F then boundary is +/-5.4 °F S If the setpoint is Between (inclusive) v -4 °F and 68 °F then boundary is +/-3.6 °F S
Include all Discharge Air configured	If the setpoint is Less than or equal to v -9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v -9.4 °F and -4 °F then boundary is +/-5.4 °F S If the setpoint is Between (inclusive) v -4 °F and 68 °F then boundary is +/-3.6 °F S If the setpoint is Greater than v 68 °F then boundary is +/-18 °F S
Include all Discharge Air configured Upload new logo file. If none is uploaded, the default will be used. Logo file: Default Browse	If the setpoint is Less than or equal to v 9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v 9.4 °F and 4 °F then boundary is +/-5.4 °F S If the setpoint is Between (inclusive) v 4 °F and 68 °F then boundary is +/-3.6 °F S If the setpoint is Greater than v 68 °F then boundary is +/-18 °F S Email full report from the current level and below to these users
Include all Discharge Air configured Upload new logo file. If none is uploaded, the default will be used. Logo file: Default	If the setpoint is Less than or equal to v 9.4 °F then boundary is +/-9 °F S If the setpoint is Between (exclusive) v 9.4 °F and 4 °F then boundary is +/-5.4 °F S If the setpoint is Between (inclusive) v 4 °F and 68 °F then boundary is +/-3.6 °F S If the setpoint is Greater than v 68 °F then boundary is +/-18 °F S Email full report from the current level and below to these users
Include all Discharge Air configured Upload new logo file. If none is uploaded, the default will be used. Logo file: Default Browse Delete logo	If the setpoint is Less than or equal to       ●9.4       oF then boundary is +/-9       oF &         If the setpoint is Between (exclusive)       ●9.4       oF and 64       oF then boundary is +/-5.4       oF &         If the setpoint is Between (inclusive)       ●4       oF and 68       oF then boundary is +/-3.6       oF &         If the setpoint is Greater than       ●68       oF then boundary is +/-18       oF &         Email full report from the current level and below to these users


Food Quality Report Configuration Screen

The configured values will be stored on the tree level from where the page was accessed (as indicated in the **Item** field). The values will then be used for any report items at the indicated level and the below levels, unless a specific set of values is set for a below level.

The Food Quality Report Configuration page is divided into two sections. The top part of the page (above "OR") shows the default settings. The bottom part (below "OR") shows the customizable settings for the indicated level and below levels. Choose one of the two sections by enabling the appropriate radio button.

The options available for the bottom section of the Configuration Page are below:

• Use rules below for calculating High and Low Limit - Enable this checkbox to include the formula rules below for case temperatures and Discharge Air (user-defined configured) instead of the rules above.



Formulas will allow the high and low boundaries on the Food Quality Report to "float" with the setpoint of the individual circuit.

Add					
If the setpoint is Less th	nan or equal to	✔ -9.4	°F then boundary is +/	/-9⁰F <b>⊗</b>	
If the setpoint is Betwee	en (exclusive)	✓ -9.4	°Fand-4	<sup>o</sup> Fthen boundary is +/-5.4	٥F
If the setpoint is Betwee	en (inclusive)	✓ -4	°Fand 68	<sup>o</sup> Fthen boundary is +/-3.6	٥F
If the setpoint is Greate	er than	✓ 68	°F then boundary is +/	′-18 °F <b>⊗</b>	

• Copy Default Rules Now - Click this button to use the default rules from the default setting.

#### Copy default rules now

Use Fixed Values For High and Low Limit (on case temperatures) - When this checkbox is selected, the formulas will be changed to fixed values. The high and low boundaries on the Food Quality Report will be fixed for this circuit regardless of the setpoint value of the circuit.

🗸 Use Fixed	d Values For High and Low Limit	
Low Limit		٥F
High Limit		٥F

- Exclude from the Report Generation for FQR When selected, the current level (usually application instance) will be excluded from the FQR.
- Exclude all Case Temperatures Enabling this option will exclude all Case temperatures for all circuits, both Case Control, Standard and XM, from the Food Quality Report.

• Include Product Simulator Probes - Enable this checkbox to include product simulator probes in the Food Quality Report. Allows configuration of the Product Temp Probes.

Use rules below for calculating High and Low Limit for Product Temp Probes Copy default rules now						
Use Fixed Values For High and Low Limit						
Add						

- Include all Discharge Air configured If this checkbox is enabled, the Discharge Air for Case Control devices will be included in the Food Quality Report.
- Exclude Related Case Temperatures Enable this checkbox to exclude Case Temperatures in the Food Quality Report for which devices have Discharge Air. Note that Case Temperatures are included by default.
- Logo file Logo file can be selected (optional).
- Email full report from the current level and below to these users Allows the selected users of this list to receive the Food Quality Report each day by email from this current level and below. Usually, this is used when the Store Manager needs to get the reports each day.

Users		
administrator @copeland.com		-
Advanced @copeland.com		- 5
advdemo @copeland.com		
advdemo@copeland.com		
AHR @copeland.com		
nicholson@copeland.com		
nicholson@copeland.com		
API @copeland.com		
Sharma@copeland.com		
Sharma@copelano.com		•
Additional Email Addresses (comma separate	ed)	•
	ed)	-
	ed)	-

Include users who currently have report emailing from above this level - When this checkbox is enabled, all users listed at the top part of the page (above "OR") will also receive the report each day. When this checkbox is disabled, only the users who are selected in the "Users" list and those in the "Additional Email Addresses" list will receive an email of the report each day. This feature is beneficial, for example, when a Regional Manager wants to receive only some reports. This report will be added at a level above this one, but this check box should be enabled only to send this report to Store Managers.

After the configuration is done. Click the Save button.

٠

# 4. FQR Data Gathering

Before the Food Quality report is generated, gather the data first. The activity can be scheduled set to execute on demand.

### 4.1 Schedule FQR Data Gathering

Go to **Top Menu > Activity > Schedule Manager**, choose Activity Type as **FQR Data Gathering**. Set the schedule detail of the activity (for example, when will the activity run for the first time, the starting and ending date and time of succeeding Smart Retries, and more). Choose the date range you want to gather, and click **Save** after the configuration is finished.

Schedule Manager					
All schedules are based on the server's time zone: (GMT -05:00) Easte	rn Standard Time -	America/New_York (EST)	(DST)		
🔿 Run Now 💿 Run On Schedule					
Details					
Enabled: 🗸					
Name:					
Type: FQR Data Gathering V					
Schedule					
- (GMT -05:00) Eastern Standard Time - America/New_Yo	rk (EST) (DST)				
Run Once Interval Based O Calendar Based					
Start Date/Time: 04/27/21 3:56 PM					
End Date/Time:					
● Every Day ○ Days of Week ○ Days of Month					
Hours 012345678910111213141516171	18 19 20 21 22 23		All	Clear	
Minutes 0 5 10 15 20 25 30 35 40 45 50 55			All	Clear	
Notification					
On Success On Unsuccessful					
Configuration					
Site Directories					
🗄 📃 🖿 Asia Demo	Generate Repo				
	Create Report				
🕂 🗖 Dan	ODate Range	Number of Days Bac			
🛓 🗌 🖿 Demo		Yesterday	~		
Dento					

#### Schedule Manager Screen

If you need to generate the report right away once data gathering is completed, you can check **Create Report PDF Files**. An electronic copy of the report will be generated under the tomcat folder **...\webapps\copeland\vault\FQR-Reports** in the server.

If the activity is on-demand, it will automatically be downloaded as a compressed package or shown as PDF on a new tab for one day of a single site. (Verify your browser is set to allow pop-ups to open) once data gathering is completed.

# 4.2 Run FQR Data Gathering One Time

FQR Data Gathering can be run on demand. Right click on directory or site, select Food Quality > FQR Data Gathering.

# 5. FQR Report Generator

### 5.1 Report Generation Activity

Before report generation, verify the data have been retrieved in Connect+.

You can generate FQR report for a directory or a site by schedule or demand. Choose **FQR Report Generation** in Schedule Manager type, or right-click on directory or site level, and select **Food Quality > FQR Report Generation**.

Schedule Manager				
All schedules are based on the server's time zone: (GMT -05:00) Eastern Standard Time	<ul> <li>America/New_York (EST) (DST)</li> </ul>			
🔿 Run Now 🛛 🖲 Run On Schedule				
Details				
Enabled: 🗹				
Name:				
Type: FQR Report Generation				
Schedule				
- (GMT -05:00) Eastern Standard Time - America/New_York (EST) (DST)				
O Run Once         O Interval Based         Image: Calendar Based           Start Date/Time:         05/07/21         1:36 PM         Y				
End Date/Time:				
Every Day				
Hours 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 2	2 23	All	Clear	
Minutes 0 5 10 15 20 25 30 35 40 45 50 55		All	Clear	
			Cicui	
Notification				
On Success On Unsuccessful				
Configuration				
Site Directories	t PDF Files			
ia ◯ ■ Asia Demo ODate Range	Number of Days Back			
	Yesterday V			
	• Hearter Mary			
© •				
🗃 🔘 🖿 Demo				



Choose the date range or the number of days that you want the report to be generated.

Date Range	ONumber of Days Back
Start Date:	
05/06/2021	
End Date:	
05/06/2021	

ODate Range	Number of Days Back
	Yesterday 🗸
	Today
	Yesterday
	2 days
	3 days
	4 days
	5 days
	6 days
	7 days
	8 days
	9 days
	10 days
	11 days
	12 days
	13 days
	14 days

.

Once all configurations are done, click Go to start the report generation activity.

The report will be generated as a PDF after the activity has completed. It is generated based on one site per day, if the reports you generated are for multiple sites or several days, they will be presented in a compressed package.

When the user selects **Today** as the **Number of Days Back or Date Range**, which includes today's date, the FQR Data Gathering activity will be executed before the report is generated. This means that the report will not be generated as quickly.

### 5.2 Food Quality Report for Yesterday

If you want to quickly generate yesterday's FQR report for review, right-click on a Directory or Site, select Food Quality > FOOD QUALITY REPORT for Yesterday.

Advis	ories
	FOOD QUALITY REPORT for Yesterday
° 🍖	FQR Data Gathering
s ត	FQR Report Generation
. 💫	Configure Food Quality Report

Food Quality Report for Yesterday

A system job will gather FQR data every day at 1:00 AM by default, but the schedule time is configurable.

Il schedules are based Schedule Assis		me zone: (GMT -0	05:00) Eastern Standard	d Time - America/New_York (EST) (D	ST)	✓ Show System Schedules	Show 25
훩 Reset Scheduler	💢 Delete All	🔾 🗿 Add New	eset Filters				
Name	Туре		User	Schedule	Next Run Time 🔺	Last Run Time	Last Status
fqr	All	~			•		All
FQRDataGatheringJo	b system		system	Every Day At 1:00 AM	5/19/21 1:00 AM	5/18/21 1:00 AM	Partially Completed
FQR Demo	FQR Dat	ta Gathering	engadmin	Every Day At 2:20 AM	5/19/21 2:20 AM	5/18/21 2:20 AM	Partially Completed
FQRReportEmailJob	system		system	Every Day At 3:40 PM	5/19/21 3:40 PM	5/18/21 3:40 PM	Completed

Schedule Assistant Screen

# 5.3 Reading the FQR Report

The report will be generated for one site per day. By default, it is named as <SiteName>\_YYYYMMDD.pdf.


If multiple reports are generated, usually for a directory or multiple day, all the reports will be zipped up into one file.

Here is an example of the report:

tem	SEPT	Low	Hiah	00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
T1 GROC (case	-12.5	-21.5	-3.5	*	6.9	-9.3	-9.3	-9.3	-9.3	*	7.4	-9.3	-9.3	-9.3	-9.3	-9.3	-9.3	-8.0	-9.3	*	7.5	-9.3	-9.3	-9.3	-9.3	-9.3	-9.3	
T2 RI FROZ FD Product 1)	1.5	-2.1	5.1	0.7	20.5	1.1	1.3	0.9	1.2	1.1	1.2	0.9	0.8	1.0	1.2	1.0	0.7	1.5	0.9	0.9	1.2	0.9	1.1	1.5	1.1	1.1	1.4	
T3 RI FROZ FD case 1)	0.5	-3.1	4.1	0.6	攀	-0.2	0.5	0.0	-0.2	0.4	-0.5	0.3	0.6	0.0	0.3	0.1	0.1	1.6	0.5	0.0	-0.1	-0.1	0.2	-0.2	0.1	0.0	0.6	
LT7 RI FROZ FD Disch Air 1: CCB_ 001)	0.0	-3.6	3.6	-0.6	0.1	0.1	0	-0.6	-0.4	-0.4	-0.5	-0.3	0.7	0.1	-0.8	-0.2	0.3	0.8	0.2	-0.2	0.0	-0.8	-0.3	-0.6	-0.5	-1.1	-0.6	
T9 SEAFD FRZR CCB 001)	0.0	-3.6	3.6	-7.5	-7.5	-7.5	-7.5	攀	-2.0	-7.5	-7.5	-7.5	-7.5	攀	-1.7	-7.5	-7.5	-6.4	-7.5	攀	-1.7	-7.5	-7.5	-7.5	-7.5	豢	-1.9	
MEAT PREP Product: CC100L_1)	50.0	46.4	53.6	47.0	47.8	*	攀	49.1	48.4	47.2	47.6	47.5	47.3	47.7	46.8	47.9	47.9	47.6	48.6	47.7	47.6	48.0	46.7	47.1	47.6	47.3	47.6	
C27 RI ICREAM	-10.0	-19.0	-1.0	攀	$\bigotimes$	$\bigotimes$	$\otimes$	$\otimes$	$\bigotimes$	$\otimes$	$\bigotimes$	$\otimes$	$\otimes$	$\otimes$	$\otimes$	*	$\otimes$	$\otimes$	$\otimes$	$\bigotimes$	$\otimes$	$\bigotimes$	$\otimes$	$\otimes$	$\otimes$	$\otimes$	$\otimes$	
C28 RI FRZ FD case 1)	-2.0	-5.6	1.6	-0.8	-0.8	-0.9	攀	-0.6	-1.0	-0.6	-0.8	-0.6	-0.6	-0.5	-0.5	-1.0	-0.7	-0.7	攀	-0.4	-1.0	-0.5	-0.8	-0.4	-0.6	-0.4	-0.6	
A15 MD MEAT case 1)	28.0	24.4	31.6	29.9	29.9	29.9	29.9	獭	29.9	29.9	29.9	29.9	29.9	攀	30.0	29.9	29.9	29.9	29.9	攀	29.9	29.9	29.9	29.9	29.9	獭	29.9	
A16 MD DAIRY case 1)	32.0	28.4	35.6	31.6	31.6	31.6	31.7	31.6	攀	31.6	31.6	31.6	31.6	31.6	*	31.6	31.6	31.6	31.6	31.6	獭	31.6	31.6	31.6	31.6	31.6	獭	
B19 MEAT HOLD case 1)	32.0	28.4	35.6	32.5	32.2	攀	34.1	32.3	32.2	32.5	32.7	攀	33.6	32.0	32.5	32.5	32.4	攀	34.2	32.4	32.2	32.3	32.0	攀	34.1	32.0	32.4	
B20 SD DAIRY case 1)	26.0	22.4	29.6	31.4	攀	34.9	31.3	30.9	31.2	31.5	攀	35.0	31.2	31.2	31.7	31.7	獭	36.8	31.4	31.3	31.1	31.3	獭	35.1	31.5	31.2	31.2	
B21A SVC PLTRY case 1)	27.0	23.4	30.6	攀	攀	31.6	31.7	31.2	31.6	31.9	31.8	31.6	31.6	31.6	32.2	32.1	31.7	31.5	31.9	31.8	31.4	31.7	31.5	32.0	32.0	31.5	31.5	
B21B SRVC MEAT case 1)	26.0	22.4	29.6	攀	攀	30.6	30.7	30.2	30.6	30.8	30.8	30.5	30.6	30.6	31.1	31.0	30.6	30.5	30.8	30.6	30.6	30.6	30.4	30.8	30.8	30.5	30.5	

#### Sample Report

1. Legend: Each report will have a legend displayed at the top of the page. Symbols and colors used in the report denote the status of a food case or circuit for a given hour.




- A cell with a white background denotes that the hourly average temperature of a case is within the High and Low limit range; the case/circuit temperature for that hour is "Normal."
- A cell with a blue background denotes the hourly average temperature of a case falls below the Low limit indicating the case/circuit was "too cold" for that certain hour.
- A cell with a red background denotes that the hourly average temperature of a case exceeds the High limit indicating the case/circuit was "too hot."
- The defrost icon 🏶 denotes that defrost occurred during that hour.
- The scheduled defrost icon 🔍 denotes that a scheduled defrost occurred for more than 10 minutes.
- Dash lines (---) denote that no log data was retrieved for the corresponding hour, indicating that the data could be retrieved later.
- The symbol 🖤 indicates that errors in data were identified for the corresponding hour, indicating that the data in the controller is either invalid or non-existent.


#### 2. Report name:



- **3.** Logo: you can change the logo from Food Quality Report Configuration (Refer to Section 3 - "Configure Food Quality Report" on page 4).
- 4. Item: The items on the left hand side are names of circuits in alphabetical order.
- The Standard Circuit/Case Circuit/XM Circuit with Case Temp: Circuit name (case #)




Standard Circuit/Case Circuit/XM Circuit with Product Temp: *Circuit name (Product #)* 



 If the Case Circuit associated with a device, the device with Case Temp will display the name as: Circuit name (Device name #)



 If the Case Circuit associated with a device, the device with Product Temp will display the name as: Circuit name (Product: Device name)



If the Standard Case Circuit associated with a device, the device with Discharge Air will display the name as: *Circuit name (Discharge Air #: Device name)* 

LT7 RI FROZ FD (Disch Air 1: CCB_
,001)

5. SEPT: It is the value of ACTIVE SETPT. If the ACTIVE SETPT configured with log, it will show the average data of the day, otherwise, it shows the real-time data of this point.

SEPT
-12.5
1.5

6. Low/High: The High and Low limit boundaries are calculated based on the Setpoint (ACTIVE SETPT) and what the user wants the range variance to be (configured in Food Quality Configuration page). These boundaries are used in the right-hand hourly columns of the report to show if the item was too hot (red background) or too cold (blue background).

Low	High
-21.5	-3.5
-2.1	5.1

7. Hourly Value: There will be 1 column on the right for each hour of the day (0-23). The value in each column for a given row is the average for that hour from the log data. If the point is not configured with a log, it is the real time data. The points from which the data is retrieved will correspond to the name found in the left column.

00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23
۰	6.9	-9.3	-9.3	-9.3	-9.3	*	7.4	-9.3	-9.3	-9.3	-9.3	-9.3	-9.3	-8.0	-9.3	拳		-9.3	-9.3	-9.3	-9.3	-9.3	-9.3
0.7	20.5	1.1	1.3	0.9	1.2	1.1	1.2	0.9	0.8	1.0	1.2	1.0	0.7	1.5	0.9	0.9	1.2	0.9	1.1	1.5	1.1	1.1	1.4
0.6	攀	-0.2	0.5	0.0	-0.2	0.4	-0.5	0.3	0.6	0.0	0.3	0.1	0.1	1.6	0.5	0.0	-0.1	-0.1	0.2	-0.2	0.1	0.0	0.6

The Defrost point log will be evaluated to determine if the defrost is present during hours of the day for the current day, and if the Defrost is present for a given

hour, the Defrost icon <sup>\*\*</sup> will show on the report. If the Defrost is configured as schedule, it will show a

scheduled defrost icon 🙂

8. Address: To show your site address at the bottom of the report, enable the FQRSystemConfigs. displayFQRSiteAddress with administrator privileges. The address will be read from **Site Configuration** page. For example:

Temperature Report for Conyers, GA. 30013

# 6. FQR Report Emailing

There are three types of FQR emails. Users can be configured to receive any of these emails depending on their roles and needs:

- a. FQR Full Report Email Sends an email with the corresponding FQRs for the site to which the user has been assigned. The FQRs are sent in PDF format as a separate files or a ZIP file (more than 3 files will combine with a ZIP file) attachment and is recommended for end-users without administrator responsibilities.
- b. FQR Summary Email Includes a table showing a summary of the reports that were run for the last seven (7) days and how many were completed successfully, as well as a table listing the sites that had exceptions for the last seven days. The information is in the body of the email without attachments and is recommended for system administrators who do not want to view entire reports and want to keep their Inbox to a minimum size.
- c. FQR Exception Details Email The same as FQR Summary email but with additional details about the type of errors for each site that had exceptions. It will also have the corresponding site reports with exceptions attached in PDF format as a ZIP file and is recommended for system administrators who want to review reports and detailed failures for each site.

The configuration procedures for these three types are described in the following sections:

### 6.1 FQR Full Report Email

The Full Report email will include all the reports that the user is allowed access to, attached as a PDF file or within a ZIP file.

Please note that the attachment report ZIP is limited to the size property FQRSystemConfigs > report.email.attachments. limit.maxKB that is configured by the administrator. It can be changed to any value for that installation that the system or email server can handle.

Before emailing, verify the below properties are configured by the administrator:

#### Table 2: Property Settings

Property Name	Set Property Value To
Mail.smtp.host	<the could="" mail="" name="" receive="" send,="" server="" that="" the=""></the>
report.email.fullReports.default.recipient.e mails	<the all="" email="" of="" person="" receive="" reports="" the="" who="" will=""></the>
report.email.from	<the address="" all="" as="" email="" emails="" for="" fqr="" from="" in="" shown="" the=""></the>

The **report.email.fullReports.default.recipient.emails** is configured for global, after it has been configured, it will display in the default section above "OR" in blue text in the FQR Configuration page, and will be inherit at directory level.

O Use default values below which are the global default values.	
Included in Food Quality Report	High/Low Limit Rules List
Logo file: Default	-> If the setpoint is Less than or equal to -9.4 $^{\rm oF}$ , then threshold is +/- 9 $^{\rm oF}$ from the setpoint .
	-> If the setpoint is Between (exclusive) -9.4 °F and -4 °F , then threshold is +/- 5.4 °F from the setpoint .
	-> If the setpoint is Between (inclusive) -4 °F and 68 °F , then threshold is +/- 3.6 °F from the setpoint .
	-> If the setpoint is Greater than 68 °F , then threshold is +/- 18 °F from the setpoint .
	FQR reports currently being emailed to these users:
	username@copeland.com
-	

#### FQR Configuration Screen

If report emailing has already been configured for a directory, the names and email addresses of the users configured for report emailing will display in the default section above "OR" in blue text for the site. If configuring report emailing for the first time, this area will be blank. To configure this functionality, follow the steps below:

- 1. Enable the Enter values specifically for this item radio button (under the "OR" section) to configure report emailing for the navigation tree level you are on.
- 2. Enable the Email full report from the current level and below to these users by configuring the radio button to configure an email list. When the checkbox is selected, a Users box will display the names and email addresses of users configured in Connect+, and the Additional Email Addresses box will appear.
- 3. Configure an email list for the current level.
- Under **Users**, enable the checkbox next to the username that you wish to add in the email list. Users will get reports only for sites that they are given permission to access. If a user is selected from the list but does not have access to a given site, the user will not receive FQR emails for that site.
- Additional email addresses may be entered into the Additional Email Addresses box. One or more email addresses can be entered. Use a comma (,) between email addresses to separate them.
- 4. (Optional) If accessing the page from a Site level and the Directory's email list needs to be added to the current Site's email list, enable the Include users who currently have report emailing from above this level checkbox. Enable this checkbox if the email address(es) above the current level should receive the report in addition to the users selected in the **User** box and the Additional Email Addresses box; otherwise, disable the checkbox to send the report only to the email addresses selected in the **User** and Additional Email Addresses boxes.

When FQR is run from this level and the report is generated, the reports will be sent out by email after a system job

Schedule Manage Il schedules are based on the Schedule Assistant	e server's time zone: (GMT -05	:00) Eastern Standard	d Time - America/New_York (EST) (DST	)	✔ Show System Schedules	Show 25
🍰 Reset Scheduler 🛛 🔀 [	Delete All 🛛 💿 Add New	eset Filters				
Name	Туре	User	Schedule	Next Run Time 🔺	Last Run Time	Last Status
İqr	All			•		All
FQRDataGatheringJob	system	system	Every Day At 1:00 AM	5/19/21 1:00 AM	5/18/21 1:00 AM	Partially Completed
FQR Demo	FQR Data Gathering	engadmin	Every Day At 2:20 AM	5/19/21 2:20 AM	5/18/21 2:20 AM	Partially Completed
FQRReportEmailJob	system	system	Every Day At 3:40 PM	5/19/21 3:40 PM	5/18/21 3:40 PM	Completed

5. Click **Save** at the top of the page.

FQRReportEmailJob is executed.

FQRReportEmailJob Sample

The email recipients list will receive an email with the report attachment. If three or less reports were generated, individual reports (PDF) will be attached to the email. If more than three reports were generated, the reports will be attached to the email as a zipped file (ZIP).

The **report.email.from** property must have a valid email-formatted address for emailing to be set up properly.

# 6.2 FQR Summary Email

The FQR Summary Email will include a table showing a summary of the reports that were run for the last seven (7) days and how many were completed successfully as well as a table listing the sites that had exceptions for the last seven days.

#### FQR Report Summary on RD-internal(RsSwdev09)

Complete & Incomplete Report Counts (A complete report means all values are filled in)

FQR Summary	Dec 05	Dec 06	Dec 07	Dec 08	Dec 09	Dec 10	Dec 11
Completed Reports	29	29	30	30	30	30	30
Incomplete Reports	3	3	2	2	2	2	2
Percent Complete	91%	91%	94%	94%	94%	94%	94%

Note: The following tables contain potential issues and may include sites that are considered complete.

#### Report Exception Counts

Items highlighted with a yellow background are incomplete reports for that day.

Site Name	Exceptions on Dec 05	Exceptions on Dec 06	Exceptions on Dec 07	Exceptions on Dec 08	Exceptions on Dec 09	Exceptions on Dec 10	Exceptions on Dec 11
506	2	1	0	0	0	0	0
530	1	1	1	1	1	1	1
538	1	1	1	0	1	1	2
539	1	1	1	1	1	1	1
545	1	0	1	0	0	0	0
556	1	1	1	1	1	1	1
562	2	3	2	3	2	2	2
575	2	2	2	2	2	2	2

#### FQR Report Summary

For the **Complete & Incomplete Report Counts** table, each of the last seven days shows a column with the most current day appearing on the far right.

Complete & Inco	mplet	te Rep	ort Co	ounts (	A com	plete	report
FQR Summary	Dec 05	Dec 06	Dec 07	Dec 08	Dec 09	Dec 10	Dec 11
Completed Reports	29	29	30	30	30	30	30
Incomplete Reports	3	3	2	2	2	2	2
Percent Complete	91%	91%	94%	94%	94%	94%	94%

#### FQR Complete and Incomplete Report Counts

- The row for *Completed Reports* shows how many FQRs were completed without data gaps.
- The row for Incomplete Reports shows how many FQRs had data gaps present.
- The row for *Percent Complete* shows how complete the total was for that day.

#### **Report Exception Counts**

Items highlighted with a yellow background are incomplete reports for that day.

Site Name	Exceptions on Dec 05	Exceptions on Dec 06	Exceptions on Dec 07	Exceptions on Dec 08	Exceptions on Dec 09	Exceptions on Dec 10	Exceptions on Dec 11
506	2	1	0	0	0	0	0
530	1	1	1	1	1	1	1
538	1	1	1	0	1	1	2
539	1	1	1	1	1	1	1
545	1	0	1	0	0	0	0
556	1	1	1	1	1	1	1
562	2	3	2	3	2	2	2
575	2	2	2	2	2	2	2

#### Report Exception Counts

- Yellow background = data gap for that day.
- White background and a number greater than 0 = a minor exception for that day.
- White background with a 0 = report was complete for that day.

One example is a defrost schedule or log was missing for that day. For the Error Message Definitions below, note that the numbers in each column represent the summation of error types, and also note that detailed error messages are only reflected in the FQR Exceptions Email:

#### Table 3: Error Message Definitions

Errors Relate	d to Defrost	Error Message As It Appears On FQR Exceptions
Defrost Log	Defrost Schedule	Emailed Report
Yes but less than 10 minutes	No	Defrost Log Data Not Found
Yes but less than 10 minutes	Yes	Defrost Log Data Not Found
No	No	Neither Defrost Log Nor Defrost Schedule Is Found
Causes For (	Other Errors	Error Message As It Appears On FQR Exceptions Email
Data gathering error - this may occ connection or transmission error.	cur due to network	Temperature Log Not Found
<ul> <li>Data Error - the data is not valid .The other than OK is reflected in the repossible errors detected are:</li> <li>No Data</li> <li>Failure on Point</li> <li>Point is Inactive</li> <li>Data is Missing</li> <li>Not Applicable</li> <li>Not Active</li> <li>No Value</li> </ul>		Invalid Temperature Log Data

Before sending the summary report, verify the below properties have been configured by the administrator.

#### Table 4: Property Settings

Property Name	Set Property Value To
report.email.isEmailExceptionReportsSummary	true
report.email.exceptionsReportsSummary.recipients	<the addresses="" email="" receive="" report="" that="" the="" will=""> (Note that these email addresses do not currently have to be users in the Connect+ system.)</the>

### 6.3 FQR Exception Email

The FQR Exception Details Email will include the same two tables as the FQR Summary Email with the additional detail of each site that had exceptions, as well as the type of exceptions. It will also have the corresponding site reports with exceptions attached in PDF format.



FQR Summary

# 7. Auto-Fix Previous Reports

When the FQR Generation job runs, it will automatically attempt to auto-repair any pending errors in reports generated on previous days. This is a default feature of the system and does not need to be enabled.

If there are pending errors/exceptions:

- The system will attempt to regenerate and auto-repair any reports with pending exceptions if missing data is found in the most recent data logs retrieved. (The table will show a maximum of 7 days, but the system will continue to search back if there are pending errors farther back than 7 days).
- Note that the system's ability to auto-repair any exceptions is limited by the controller's log memory setting. For example, if there is an error 21 days ago, but the controller is set to maintain only 2 weeks (14 days) of log data, the error cannot be auto-repaired past day 14, even if the condition causing the error (for example, a network communication problem) has been cleared.

FQR Summary	Sep 24	Sep 25	Sep 26	Sep 27	Sep 28	Sep 29	Sep 30
Completed Reports	32	31	32	32	32	32	32
Incomplete Reports	1	2	1	1	1	1	1
Percent Complete	97%	94%	97%	97%	97%	97%	97%

FQR Summary

Visit our website at copeland.com/en-us/products/controls-monitoring-systems for the latest technical documentation and updates. For Technical Support call 833-409-7505 or email ColdChain.TechnicalServices@Copeland.com

The contents of this publication are presented for informational purposes only and they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. Copeland reserves the right to modify the designs or specifications of such products at any time without notice. Responsibility for proper selection, use and maintenance of any product remains solely with the purchaser and end-user. ©2024 Copeland is a trademark of Copeland LP.

